
MATERIAL SAFETY DATA SHEET

SECTION 01 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION:

Chemical Name: **BL PLATINUM URETHANE SEALANT / ADHESIVE**
Manufacturer: **Great North Landscape Products**
Division of Snapedge Canada Ltd.
4 – 2300 Shirley Drive
Kitchener, ON N2B 3Y2
Tel: (519) 745-9996
Fax: (519) 745-8028
Emergency Tel: (800) 720-7627
After Hours: (519) 580-6113
Date: January 31st, 2014
Prepared by: Technical Services Department
WHMIS Classification: D2A, D2B
Product Use: Polyurethane Adhesive

SECTION 02 – COMPOSITION / INFORMATION ON INGREDIENTS:

<u>Ingredients-</u>	<u>CAS</u> <u>No.</u>	<u>%</u>	<u>LD50(Oral-Rat)</u>	<u>LC50(Inhalation-</u>
Calcium Carbonate	1317-65-3	10.0 – 30.0	6,450 mg/kg	Not available
Titanium Dioxide	13463-67-7	3.0 – 7.0	24,000 mg/kg	Not available
Talc	14807-96-6	1.0 – 5.0	Not available	Not available
Calcium Oxide	1305-78-8	1.0 – 5.0	7,340 mg/kg	Not available
Stoddard Solvent	8052-41-3	1.0 – 5.0	5,000 mg/kg	5,500 mg/kg (4 h)
Methyl Oleate	112-62-9	1.0 – 5.0	Not available	Not available
2,2'-Dimorpholinyl-diethylether	6425-39-4	0.5 – 1.5	2,000 mg/kg	Not available
Toluene-2,4-Diisocyanate	584-84-9	0.1 – 1.0	Not available	Not available
Silica, Quartz	14808-60-7	0.1 – 1.0	Not available	Not available

The ingredients listed above are controlled products as defined in CPR, am. SOR/88-555 or 29 CFR 1910.1200

SECTION 03 – HAZARDS IDENTIFICATION:

ROUTES OF ENTRY INTO THE BODY (ACUTE EFFECTS):

Eyes: Causes eye irritation. May cause reversible corneal injury.
Skin: Causes skin irritation. Prolonged or repeated skin contact may cause sensitization or allergic reactions.
Inhalation: Causes respiratory tract irritation. May be harmful if inhaled and may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the occupational exposure limit. Repeated inhalation may lead to a permanent respiratory disability.
Ingestion: Swallowing large amounts may be harmful with irritation of mouth, throat and stomach.

WHMIS HAZARD SYMBOL(S):



SECTION 04 - FIRST AID MEASURES:

Eyes: Flush with copious quantities of lukewarm water. Seek medical attention immediately.

Skin: Remove contaminated clothing. Use of a mild solvent, such as mineral spirits, may help in removing uncured residue from clothing or other surfaces (avoid eye/skin contact). Wash thoroughly with warm water and non-abrasive soap. Seek medical attention if you feel ill or a reaction develops.

Inhalation: Remove to fresh air and provide water. Seek medical attention if you feel ill or a reaction develops.

Ingestion: Get immediate medical attention.

SECTION 05 - FIRE FIGHTING MEASURES:

Flammable Conditions: Avoid direct sources of heat or ignition in uncured state.

Extinguishing Media: Carbon dioxide, dry chemical, water fog or foam. Water can be used to cool fire exposed containers. Water stream directed into fire may cause frothing with subsequent spread of fire.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan.

Flash Point: Not applicable - solid

Flammability Limits: Not available

Autoignition Temperature: Not available

Hazardous Decomposition Products: Carbon oxides, nitrogen oxides and traces of incompletely burned carbon products.

Sensitivity - Impact: None

Static: None

SECTION 06 - ACCIDENTAL RELEASE MEASURES:

Containment / Clean Up: Restrict access to the area of the spill. Provide ventilation and protective clothing. Scrape up adhesive and place in container for disposal. Clean area as appropriate since the adhesive may represent a slip hazard. Cleaning may require detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state, provincial, federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup.

SECTION 07 - HANDLING AND STORAGE:

Handling and Storage: Store in an adequately ventilated area under dry conditions between 50°F (10°C) to 77°F (25°C) and keep container tightly sealed when not in use.

SECTION 08 - EXPOSURE CONTROL / PERSONAL PROTECTION:

Component Exposure Limits:

Calcium Carbonate (CAS# 1317-65-3): Although the calcium carbonate is coated with the urethane resin observe the particulate limits. ACGIH TLV: TWA 10 mg/m³ inhalable particulate, 5 mg/m³ respirable particulate.

Titanium Dioxide (CAS# 13463-67-7): Although the titanium dioxide is coated with the urethane resin observe the particulate limits. OSHA PEL: TWA 15 mg/m³. ACGIH TLV: TWA 10 mg/m³.

Talc (CAS# 14807-96-6): Although the talc is coated with the urethane resin observe the particulate limits. OSHA PEL: 5 mg/m³ ACGIH TLV: TWA 2 mg/m³ respirable fraction.

Calcium Oxide (CAS# 1305-78-8): Although the calcium oxide is coated with the urethane resin observe the particulate limits. OSHA PEL: 5 mg/m³ ACGIH TLV: TWA 2 mg/m³ respirable fraction.

Stoddard Solvent (CAS# 8052-41-3): Provide adequate ventilation to control exposures within the following exposure guidelines: OSHA PEL: 500 ppm. ACGIH TLV: 100 ppm (TWA).

Toluene-2,4-Diisocyanate (CAS# 584-84-9): Provide adequate ventilation to control exposures within the following exposure guidelines: OSHA CLV: 0.02 ppm. ACGIH TLV: 0.005 ppm (TWA); STEL 0.02 ppm.

Silica, Quartz (CAS# 14808-60-7): Although the quartz is a naturally occurring component of calcium carbonate and talc and is coated with the urethane resin observe the particulate limits. OSHA PEL: TWA 0.3 mg/m³

total dust, 0.1 mg/m³ respirable fraction. ACGIH TLV: TWA 0.1 mg/m³ respirable fraction.

Respiratory: Wear a NIOSH / MSHA approved respirator when exposure limits are exceeded.

Ventilation: In indoor applications, passive ventilation (opening of doors and windows) is recommended. Local exhaust as necessary to keep exposure levels within guidelines.

Personal Protective Equipment: Safety glasses with side-protection, impermeable gloves (e.g., neoprene, nitrile, silver shield (R)), coveralls or apron are important in preventing contamination of eyes, skin and clothing. Wash thoroughly after handling.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Paste
Odor and Appearance: Aluminum grey material with mild odor
Odor Threshold: Not available
Specific Gravity: 1.21
Vapor Pressure: Not available
Vapor Density: Heavier than air
Evaporation Rate: Slower than Butyl Acetate
Boiling Point: Not available
Freezing Point: Not available
pH: Not available
Coeff. Oil/Water Distribution: Not available

SECTION 10 – STABILITY AND REACTIVITY:

Chemical Stability: Stable under normal temperature and pressure.
Incompatible Materials: Strong oxidizing agents or electrophiles and bases or acids. Alcohols and amine hardeners.
Reactive Conditions: Moisture and incompatible materials.
Hazardous Polymerization: Will not occur when handled properly.

SECTION 11 - TOXICOLOGICAL INFORMATION:

Effects of overexposure: Repeated and prolonged overexposure to isocyanates can result in effects including allergic skin and/or respiratory sensitization. Silica, Quartz (CAS #14808-60-7) is a naturally occurring component of calcium carbonate and talc and is coated with the urethane resin, however, prolonged overexposure to quartz dust causes fibrotic lung disease (silicosis) and potentially lung cancer. Although the titanium dioxide (CAS# 13463-67-7) is coated with the urethane resin, prolonged overexposure to titanium dioxide dust causes tightness pain in the chest, coughing and difficulty breathing.

Sensitization: May cause sensitization by inhalation and skin contact. Individuals previously sensitized to isocyanates should take proper precautions against further exposure.

Carcinogenicity: Silica, Quartz (CAS #14808-60-7): IARC Group 1 – Carcinogenic to Humans; NTP – Reasonably Anticipated to be a Human Carcinogen; ACGIH A2 – Suspected Human Carcinogen. Titanium Dioxide (CAS# 13463-67-7): IARC Group 2B – possibly carcinogenic to humans.

Reproductive Toxicity: No known applicable information.
Teratogenicity: No known applicable information.
Mutagenicity: No known applicable information.
Synergistic Products: No known applicable information.

SECTION 12 – ECOLOGICAL INFORMATION:

Air: Complete information is not yet available.
Water: Complete information is not yet available.
Soil: Complete information is not yet available.

SECTION 13 – DISPOSAL CONSIDERATIONS:

Waste Disposal: Dispose in accordance with Federal, State / Provincial and local regulations.

SECTION 14 - TRANSPORT INFORMATION:

Shipping Information: Classified as combustible liquid in containers greater than 119 gallons under DOT Regulations. Not classified as a dangerous good under IMDG or IATA Regulations.

SECTION 15 - REGULATORY INFORMATION:

TSCA Inventory Status: Chemical components listed on TSCA inventory except as exempted.
NFPA Profile: Health 2, Flammability 2, Reactivity 0
SARA TITLE III Chemical Listings: Section 311/312 Hazard Class (40 CFR 370): Acute: Yes; Chronic: Yes; Fire: No; Pressure: No; Reactive: Yes
State Substance List: This product contains a listed substance(s) that appears on one or more of the Substance Lists for Pennsylvania, Massachusetts, Minnesota, Rhode Island and New Jersey: calcium carbonate (CAS# 1317-65-3); titanium dioxide (CAS# 13463-67-7); talc (CAS# 14807-96-6); calcium oxide (CAS# 1305-78-8); methyl oleate (CAS# 112-62-9); toluene-2,4-diisocyanate (CAS# 584-84-9) and silica, quartz (CAS #14808-60-7).
California Proposition 65 List: Silica, Quartz (CAS #14808-60-7) is naturally occurring in the calcium carbonate and talc and is not a hazard under normal conditions of use.
Volatile Organic Content: 43 g/L (0.36 lbs/gal), less water and exempt solvents
Domestic Substance List: Chemical components listed on DSL except as exempted.

SECTION 16 - OTHER INFORMATION:

The information herein is given in good faith, but no warranty, express or implied, is made. Product users should make independent judgements of the suitability of this information to ensure proper use and to protect the health and safety of employees.

Form: MSDS BL PLATINUM SEALANT / ADHESIVE Rev.: 0 Date: 1/14